

BULK INCANDESCENT ROPE LIGHT



FEATURES

- Cost-effective lighting for a variety of applications
- Bright, colorful, flexible and versatile linear lighting product
- Field-cutttable every 24" (non-rated) for maximum project flexibility
- Available in 10 different colors
- 150 foot bulk reels that use existing, pre-connected power connection are UL rated – any rope light cut in the field is no longer UL rated

ORDERING INFORMATION

033		037	
Bulk Incandescent Rope Light	AM = Amber BL = Blue CL = Clear FR = Frosted GR = Green PI = Pink PU = Purple RE = Red YE = Yellow YE/GR = Yellow/Green	Bulk Incandescent Accessories	0001 = Non-UL six foot power cord connector kit 0002 = Non-UL splice connector 0003 = Non-UL barbed invisible splice 0004 = Non-UL 15' power cord connector kit 0005 = Non-UL invisible splice 0006 = Non-UL 2' rope to rope extension 0007 = Non-UL 2' power cord connector kit 0008 = Non-UL 15' rope to rope extension 0009 = Non-UL power connector 0010 = Non-UL 'T' connector

Example of finished order – 033-BL

TECHNICAL SPECIFICATIONS

Voltage	120V, 60Hz AC operation
Construction	UV resistant Clear PVC housing with Incandescent lamps spaced every 1.09"
Dimensions	1/2" diameter
Bulk reel	150 feet
Cuttability	Cutttable every 24"
Wattage	5.0 watts per foot
Maximum run	150 feet
Packaging	White box, full reel quantities only
Accessories	DL-CLIP = Clear mounting clip, DL-END = non-UL Clear end cap, DL-ST = Clear shrink tube, sold by the foot, DL-TRACK-4 = Four foot Clear plastic mounting track
Animation	1, 2, 3, and 4 channel controllers and cross-faders enable animated effects. Controllers illuminate from 1 to 4 separate rope light sections in a sequence (1-2-3-4) with user-controlled speed setting (CON-capacity-# of channels). Cross-Faders dim one channel while slowly illuminating the next and come in 2 or 4 channel versions. User control cross-fade speed (X-FADER-capacity-2/4CS).
Bulb Specs	25,000 hour rated life, 6.5V, 70mA
Dimmers	Dimmable with most Incandescent dimmers – be sure to use high capacity type for loads over 600 watts
Diffuser	Clear PVC jacket