



Plastic-Covered, Shatter-Resistant U-Shaped Fluorescent Lamps



The Safest
Choice for
2' x 2' Luminaires

*Provides nearly the same light output
as a linear straight lamp of twice the length.*



T-8 U-Shaped Medium BiPin with 6" leg

| Nominal Watts | Ordering Description | UPC/ Catalog# | Pkg. Qty. | Description | Nominal Length | Rated Average Life (hours) | Initial Lumens | Design Lumens | CRI |
|---------------|----------------------|---------------|-----------|-----------------------------------|----------------|----------------------------|----------------|---------------|-----|
| 32 | FB32T8/830/6 | 78528 | 20 | U-Shaped, 3000K, 6" spacing, ALTO | 22 7/16" | 20,000 | 2800 | 2535 | 85 |
| 32 | FB32T8/835/6 | 78538 | 20 | U-Shaped, 3500K, 6" spacing, ALTO | 22 7/16" | 20,000 | 2800 | 2535 | 85 |
| 32 | FB32T8/841/6 | 78548 | 20 | U-Shaped, 4100K, 6" spacing, ALTO | 22 7/16" | 20,000 | 2800 | 2535 | 85 |
| 32 | FB32T8/850/6 | 78248 | 20 | U-Shaped, 5000K, 6" spacing, ALTO | 22 7/16" | 20,000 | 2750 | 2500 | 85 |
| 32 | FB32T8/730/6 | 78498 | 20 | U-Shaped, 3000K, 6" spacing, ALTO | 22 7/16" | 20,000 | 2650 | 2370 | 75 |
| 32 | FB32T8/735/6 | 78500 | 20 | U-Shaped, 3500K, 6" spacing, ALTO | 22 7/16" | 20,000 | 2650 | 2370 | 75 |
| 32 | FB32T8/741/6 | 78510 | 20 | U-Shaped, 4100K, 6" spacing, ALTO | 22 7/16" | 20,000 | 2650 | 2370 | 75 |
| 32 | FB32T8/750/6 | 78488 | 20 | U-Shaped, 5000K, 6" spacing, ALTO | 22 7/16" | 20,000 | 2600 | 2325 | 75 |

T-12 U-Shaped Medium BiPin with 6" leg

| Nominal Watts | Ordering Description | UPC/ Catalog# | Pkg. Qty. | Description | Nominal Length | Rated Average Life (hours) | Initial Lumens | CRI |
|---------------|----------------------|---------------|-----------|---|----------------|----------------------------|----------------|-----|
| 34 | FB40T12/730/6/ES | 81491S | 12 | U-Shaped, 3000K, 6" spacing, Energy Saver | 22 1/2" | 18,000 | 2730 | 70 |
| 34 | FB40T12/735/6/ES | 81501S | 12 | U-Shaped, 3500K, 6" spacing, Energy Saver | 22 1/2" | 18,000 | 2730 | 70 |
| 34 | FB40T12/741/6/ES | 81511S | 12 | U-Shaped, 4100K, 6" spacing, Energy Saver | 22 1/2" | 18,000 | 2730 | 70 |
| 34 | FB40T12/CW/6/ES | 81011S | 12 | U-Shaped, 4200K, Cool White, 6" spacing, Energy Saver | 22 1/2" | 18,000 | 2730 | 70 |
| 34 | FB40T12/WW/6/ES | 81031S | 12 | U-Shaped, 3000K, Warm White, 6" spacing, Energy Saver | 22 1/2" | 18,000 | 2730 | 70 |
| 40 | FB40T12/830/6 | 81520S | 12 | U-Shaped, 3000K, 6" spacing | 22 1/2" | 18,000 | 3200 | 80 |
| 40 | FB40T12/730/6 | 81490S | 12 | U-Shaped, 3000K, 6" spacing | 22 1/2" | 18,000 | 3200 | 70 |
| 40 | FB40T12/735/6 | 81500S | 12 | U-Shaped, 3500K, 6" spacing | 22 1/2" | 18,000 | 3200 | 70 |
| 40 | FB40T12/741/6 | 81270S | 12 | U-Shaped, 4100K, 6" spacing | 22 1/2" | 18,000 | 3200 | 70 |
| 40 | FB40T12/CWX/6 | 81040S | 12 | U-Shaped, 4100K, 6" spacing | 22 1/2" | 18,000 | 3200 | 87 |

Available through:

www.shat-r-shield.com
1-800-223-0853